

Part Number: 5340FT



Thermostat & Control, #18-2c, TC, O/A Foil, CMR

# **Product Description**

Thermostat & Control Cable, Riser-CMR, 1-18 AWG stranded tinned copper pair with foam polyolefin insulation, Beldfoil® shield, PVC jacket

## **Technical Specifications**

### **Physical Characteristics (Overall)**

## Conductor Material AWG Stranding No. of Pairs 7x26 TC - Tinned Copper 1 Conductor Count: 2 18 AWG Conductor Size: Insulation Material Trade Name FHDPE - Foamed High Density Polyethylene Datalene® **Color Chart** Number Color Black & White

### **Outer Shield Material**

Туре	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	Aluminum/Polyester	Beldfoil®	100 %	TC - Tinned Copper	18	Solid

### **Outer Jacket Material**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.26 in

## **Electrical Characteristics**

### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR
6.6 Ohm/1000ft	16.9 Ohm/1000ft

#### Capacitance



Shielding: Foil(s) or Copper Tape(s)

## Inductance

Nominal Inductanc 0.21 µH/ft

### Impedance

Nominal Characteristic Impedance	Nominal Characteristic Tolerance
100 Ohm	± 22 Ohm

### Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
78 ns/100m	78 %

#### Current

Max. Recommended Current [A] 8.1 Amps per conductor @ 25°C A

### Voltage

UL Voltage Rating 300 V RMS

## **Temperature Range**

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

#### **Mechanical Characteristics**

Bulk Cable Weight:	26 lbs/1000ft
Max Recommended Pulling Tension:	67 lbs
Min Bend Radius/Minor Axis:	2.6 in

#### **Standards**

NE	EC/(UL) Specification:	CMR
CE	EC/C(UL) Specification:	CMG

### **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2006-02-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

C(UL) Flammability:	FT4
UL Flammability:	UL1666 Riser
UL voltage rating:	300 V RMS

#### Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6340FT

### **Part Number**

#### Variants

Item #	Color	Footnote
5340FT 0011000	Brown	С
Footnote:		

#### © 2018 Belden, Inc

## All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.